



Electrolux

Digital Undercounter Benefit-Line Refrigerated Counter 3 Doors - Stainless Steel

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Electrolux

Benefit-Line Refrigerated Counter 3 Doors - Stainless Steel
Digital Undercounter



Digital Undercounter

Benefit-Line Refrigerated Counter 3 Doors -
Stainless Steel

727642 (RCSN3M34E)

3-door refrigerated
counter, -2/+10°C, stainless
steel

Short Form Specification

Item No.

Internal and external structure, bottom, doors, front and side panels, base and removable worktop (50mm thick) in stainless steel. External back panel in galvanized steel. Reversible self-closing doors in positions less than 90°, a stop at 95° and maximum opening at 180° with a door seal guaranteeing a perfect closure. Height adjustable legs from -10/+60 in 304 AISI stainless steel. Insulation guaranteed by cyclopentane insulating foam (50mm thick). Digital control panel. Operating temperature -2/+10°C. Automatic defrosting and evaporation of defrosted water using a hot gas. Built-in refrigeration unit to operate in ambient temperatures up to +43°C. Ventilated. R404a gas in refrigeration circuit. CFC and HCFC free. Supplied with n.3 Rilsan coated grids 1/1GN.

Main Features

- Digital control panel allowing the easy and precise setting and control of the internal temperature.
- Operating temperature can be adjusted from -2 to +10 °C to suit different food storage requirements.
- Suitable for use in ambient temperatures of up to 43 °C.
- Complies with main international certification bodies and is CE marked.
- Kit 1/2 drawers available as accessory.
- The door self-closes when opened less than at a 90° angle and is equipped with a door seal to guarantee perfect closure.
- Completely automatic defrosting and automatic evaporation of defrost water by hot gas.
- Forced air cooling system guaranteeing great uniformity of the temperature in the counter and excellent conservation of the food quality.
- High standards of hygiene and ease of cleaning are guaranteed by the rounded internal corners of the cabinet and easily removable runners and grids.

Construction

- Refrigerant type: R404a.
- Built-in compressor to suit operating conditions.
- CFC and HCFC free.
- Legs in 304 AISI stainless steel (150 mm high, adjustable in height), with plastic interior.
- Insulation guaranteed by high density expanded cyclopentane 50 mm in thickness.
- Internal and external structure, bottom, doors, front and side panels, base and 50mm thick removable worktop in stainless steel.
- Back panel in galvanized steel.

Included Accessories

- 3 of 1/1GN grey rilsan grid PNC 881435

Optional Accessories

- 2 half drawers kit for Benefit line counters PNC 880023
- Lock kit for Benefit line counters PNC 880024
- Wheels kit PNC 880025
- Reversibility door kit PNC 880046
- Internal structure to support 3 grids (right and left) PNC 880047
- Kit 2 stainless steel grids GN1/1 for refrigerated counters PNC 880139
- Stainless steel internal structure to support 6 grids (right and left) PNC 880140
- Kit integrated HACCP for digital refrigerators (IR33) PNC 880252
- KIT 4 FEET FOR SB&CONCEPT COUNTER PNC 880334
- Kit reversible door for standard benefit counters PNC 880341

APPROVAL: _____



Electrolux

**Digital Undercounter
Benefit-Line Refrigerated Counter 3
Doors - Stainless Steel**


- 1/1GN plastic container h=65mm PNC 881038
- 1/1GN plastic container h=150mm PNC 881040
- 1/1GN grey rilsan grid PNC 881435
- Printer for HACCP basic version (for cabinets and counters with digital control) PNC 881457



**Digital Undercounter
Benefit-Line Refrigerated Counter 3 Doors - Stainless Steel**

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2016.07.19



Electric

Supply voltage:	727642 (RCSN3M34E)	230 V/1N ph/50 Hz
Electrical power:		0.267 kW

Key Information:

Gross capacity:	415 lt
N° of doors:	3
Door hinges:	1 Left+2 Right
External dimensions, Height:	850 mm
External dimensions, Width:	1721 mm
External dimensions, Depth with Doors Open:	1102 mm
Internal Dimensions (depth):	580 mm
Internal Dimensions (height):	543 mm
Internal Dimensions (width):	365 mm
Net weight:	115 kg
Noise level:	55 dBA
Number and type of grids (included):	3 - GN 1/1
Built-in Compressor and Refrigeration Unit	

Refrigeration Data

Control type:	Digital
Compressor power:	1/3 hp
Refrigerant type:	R404a
Refrigeration power:	448 W
Refrigeration power at evaporation temperature:	-10 °C
Refrigerant weight:	160 g
Min/Max internal humidity:	50/
Operating temperature min.:	-2 °C
Operating temperature max.:	10 °C
Operating mode:	Ventilated
N° defrost in 24 hrs:	every 6 hrs