

myPRO Edge

Washer extractor

WE2-9

Perfect for businesses with steady daily laundry needs, up to 4 cycles per day, such as

- Hotels, bed & breakfasts, and guesthouses
- Restaurants, cafés, and food-service operators
- Kindergartens, nurseries, daycare
- Hairdressing, beauty, and wellness salons
- Sports, fitness, and leisure facilities
- Cleaning and facility-management companies
- Out-of-home resident services, care environments, veterinary clinics and many more

Features and benefits

- Plug-and-play installation with 9 kg capacity and flexible setup options, including pump or gravity-valve configurations^I
- Best wash results and garment care due to unique professional drum with 4.5 mm holes for efficient evacuation of debris^I
- Triple lifetime^{II} ensuring a minimum of 7,500 cycles, based on the recommended maximum of 4 cycles per day
- Professional program selection including specialized disinfection, mop and steam programs
- Up to half the cycle time^{II}, delivering high performance in a compact footprint
- Time saver: Cotton 60°C completed in just 75 minutes using the hot water inlet, reducing cycle time by 17 minutes compared to cold water
- Stainless-steel front and top panels contribute to robust, long-term reliability
- Fully compliant with EU Machinery Directive 2006/42/EC, ensuring safe and appropriate commercial use

^I. Ideal for facility management and care segment.

^{II}. Compared to domestic machines.

Accessories

- Base with pull out drawer
- Stacking kit with pull out shelf
- Liquid detergent dosing external connection box
- Marine kit



Main specifications		WE2-9
Washing capacity	kg	9
Drum, volume	l	70
Energy efficiency class		A
Consumption data ¹		
Total time (hot inlet)	min./cycle	75
Energy consumption (hot inlet)	kW	0.7
Total water consumption	l	68

¹. Cotton 60, 100% cotton 9 kg

Feature		WE2-9
Spin speed	rpm / G-factor	1.400 / 536
Total power	kW	2.2
Main voltage	V	200 / 220-240*
Frequency	Hz	50 / 60*
Water inlet		Hot & cold
Draining system		Drain pump / drain valve*
Detergent compartments		3
Drum light		LED
Levelling feet		4 adjustable feet (adjustable by 15 mm)
Number of programs		16
Number of additional functions		6
Program proportionality		Adapts to full or partial load

*Availability of configurations varies by market.

Dimensions		WE2-9
Weight	kg	80.5
Weight, with packaging	kg	82
Packaging height	mm	900
Packaging width	mm	640
Packaging depth	mm	710
Height (A)*	mm	847
Width (B)*	mm	597
Depth (C)*	mm	619

* Dimensions (including door frame).

