

myPRO Go

Washer extractor

WE2-9PS

Perfect for businesses with steady daily laundry needs, up to 4 cycles per day, such as

- Hotels, camping, B&B
- Out-of-home resident services - sheltered housing
- Mining, marine and military and many more

Features and benefits

- Plug-and-play installation with 9 kg capacity and flexible setup options, including pump or gravity-valve configurations^I
- Best wash results and garment care due to unique professional drum with 4.5 mm holes for efficient evacuation of debris^I
- Triple lifetime^{II} ensuring a minimum of 7,500 cycles, based on the recommended maximum of 4 cycles per day
- Payment-system ready, making it ideal for pay-per-use installations
- Ultra-simple control interface with only 6 programs, including specialized steam program
- Up to half the cycle time^{II}, delivering high performance in a compact footprint
- Time saver: Cotton 60°C completed in just 75 minutes using the hot water inlet, reducing cycle time by 17 minutes compared to cold water
- Stainless-steel front and top panels contribute to robust, long-term reliability
- Fully compliant with EU Machinery Directive 2006/42/EC, ensuring safe and appropriate commercial use

I. Ideal for facility management and care segment.
II. Compared to domestic machines.

Accessories

- Base with pull out drawer
- Stacking kit with pull out shelf
- Coin box, coin meter, external payment harness



Main specifications		WE2-9PS
Washing capacity	kg	9
Drum, volume	l	70
Energy efficiency class		A
Consumption data ¹		
Total time (hot inlet)	min./cycle	75
Energy consumption (hot inlet)	kW	0.7
Total water consumption	l	68

1. Cotton 60, 100% cotton 9 kg

Feature		WE2-9PS
Spin speed	rpm / G-factor	1.400 / 536
Total power	kW	2.2
Main voltage	V	220-240
Frequency	Hz	50
Water inlet		Hot & cold
Draining system		Drain pump
Detergent compartments		3
Drum light		LED
Levelling feet		4 adjustable feet (adjustable by 15 mm)
Number of programs		6
Program proportionality		Adapts to full or non-full load

Dimensions		WE2-9PS
Weight	kg	80.5
Weight, with packaging	kg	82
Packaging height	mm	900
Packaging width	mm	640
Packaging depth	mm	710
Height (A)*	mm	847
Width (B)*	mm	597
Depth (C)*	mm	619

* Dimensions (including door frame).

