

myPRO Edge

Heat pump dryer

TD2-9HP

Perfect for businesses with steady daily laundry needs, up to 4 cycles per day, such as

- Hotels, bed & breakfasts, and guesthouses
- Restaurants, cafés, and food-service operators
- Kindergartens, nurseries, daycare
- Hairdressing, beauty, and wellness salons
- Sports, fitness, and leisure facilities
- Cleaning and facility-management companies
- Out-of-home resident services, care environments, veterinary clinics and many more

Features and benefits

- Plug-and-play installation with 9 kg capacity and 16 drying programs to meet every need
- Triple lifetime¹ ensuring a minimum of 7,500 cycles, based on the recommended maximum of 4 cycles per day
- Gentle on textiles thanks to low-temperature heat-pump drying, while Residual Moisture Control prevents over-drying and saves energy
- Save up to 60% energy compared to vented and condenser dryers thanks to efficient heat-pump technology
- Environmentally friendly design using R290 refrigerant
- Stainless-steel front and top panels contribute to robust, long-term reliability
- Fully compliant with EU Machinery Directive 2006/42/EC, ensuring safe and appropriate commercial use

I. Compared to domestic machines.

Accessories

- Pedestal with pull out drawer
- Stacking kit with pull out shelf
- Marine kit



Main specifications		TD2-9HP
Drying capacity	kg	9
Drum, volume	l	120
Energy efficiency class		D
Condensation efficiency		C (85%)
Consumption data ¹		
Total time	min./cycle	149
Energy consumption	kW	2.05

1. Program Normal Dry (initial RM% 50%) 100% cotton, 9 kg

Feature	TD2-9HP
Drying technology	Heat pump
Total power	kW 0.9
Main voltage	V 220-240
Frequency	Hz 50
Declared drying noise	dB(A) 66
Heat emissions (at 20°C ambient)	W 800
Refrigerant gas	R290 (Hydrocarbon, hermetically sealed)
Gas weight	kg 0.149
Levelling feet	4 adjustable feet (adjustable by 15 mm)
Global-warming potential (GWP)*	0.02
Drum light	LED
Levelling feet	4 adjustable feet (adjustable by 15 mm)
Number of programs	16
Additional functions	6

*According to IPCC AR6.

Dimensions	TD2-9HP
Weight	kg 50
Weight, with packaging	kg 51.5
Packaging height	mm 890
Packaging width	mm 640
Packaging depth	mm 680
Height (A)*	mm 850
Width (B)*	mm 596
Depth (C)*	mm 615

* Dimensions (including door frame).

