

myPRO Edge

Tumble dryer

TD2-8

Perfect for businesses with steady daily laundry needs, up to 4 cycles per day, such as

- Hotels, bed & breakfasts, and guesthouses
- Restaurants, cafés, and food-service operators
- Kindergartens, nurseries, daycare
- Hairdressing, beauty, and wellness salons
- Sports, fitness, and leisure facilities
- Cleaning and facility-management companies
- Out-of-home resident services, care environments, veterinary clinics
- Mining, marine and military and many more

Features and benefits

- Plug-and-play installation with 8 kg capacity and 16 drying programs to meet every need
- Triple lifetime¹ ensuring a minimum of 7,500 cycles, based on the recommended maximum of 4 cycles per day
- Improved convenience with an optional direct drain connection from the condensed-water tank for continuous discharge
- Stainless-steel front and top panels contribute to robust, long-term reliability
- Fully compliant with EU Machinery Directive 2006/42/EC, ensuring safe and appropriate commercial use

1. Compared to domestic machines.

Accessories

- Pedestal with pull out drawer
- Stacking kit with pull out shelf
- Coin box, coin meter, external payment harness



Main specifications		TD2-8
Drying capacity	kg	8
Drum, volume	l	120
Condensation efficiency		A (>90%)
Consumption data ¹		
Total time	min./cycle	89
Energy consumption	kW	4.88

1. Program Normal Dry (initial RM% 50%) 100% cotton, 9 kg

Feature	TD2-8
Drying technology	Condense (electric heating elements)
Total power	kW 2.8
Main voltage	V 200 / 220-240*
Frequency	Hz 50 / 60*
Declared drying noise	dB(A) < 70
Filter	With handle for easier removal
Filter sensor	Machine does not start if filter is not in position
Drum light	LED
Levelling feet	4 adjustable feet (adjustable by 15 mm)
Number of programs	16
Additional functions	6

*Availability of configurations varies by market .

Dimensions	TD2-8
Weight	kg 40.7
Weight, with packaging	kg 43.3
Packaging height	mm 890
Packaging width	mm 640
Packaging depth	mm 680
Height (A)*	mm 850
Width (B)*	mm 596
Depth (C)*	mm 615

* Dimensions (including door frame).

